



# PRODUCT RANGE

“We don’t just **sell products**; we provide **complete solutions** to your fluid control problems”

SCAN ME



WS QR CODE



## CONTROL VALVE

|                 |                                     |
|-----------------|-------------------------------------|
| Size            | NPS 0.5 to NPS 24 (DN15 to DN600)   |
| Pressure Rating | CL150 to CL2500                     |
| Design Standard | ASME B16.34; ISA 75.01.01           |
| Body Material   | A216 WCB; A217 WC6 / WC9; A351 CF8M |
| End Connections | Flanged / Socket Weld / Butt Weld   |
| Leakage Class   | Class IV / Class V / Class VI       |
| Operation       | Pneumatic / Motorized / Manual      |

## 3 - WAY GLOBE VALVE

|                 |                                     |
|-----------------|-------------------------------------|
| Size            | NPS 1 to NPS 24 (DN25 to DN600)     |
| Pressure Rating | CL150 to CL2500                     |
| Design Standard | ASME B16.34; ISA 75.01.01           |
| Body Material   | A216 WCB; A217 WC6 / WC9; A351 CF8M |
| End Connections | Flanged / Socket Weld / Butt Weld   |
| Leakage Class   | Class IV / Class V                  |
| Operation       | Pneumatic / Motorized / Manual      |
| Duty            | Control / On-Off                    |
| Types           | Diverting / Mixing                  |



## BLOWDOWN VALVE (CBD/IBD)

|                 |                                     |
|-----------------|-------------------------------------|
| Size            | NPS 1 to NPS 3 (DN25 to DN80)       |
| Pressure Rating | CL300 to CL2500                     |
| Body Material   | A105; A182 F11 / F22 / F91 / F316   |
| End Connections | Flanged / Socket Weld / Butt Weld   |
| Leakage Class   | Class IV / Class V                  |
| Operation       | Motorized / Lever Operated / Manual |

## DESUPERHEATER / ATTEMPERATOR

|                 |                                                  |
|-----------------|--------------------------------------------------|
| Steam Line Size | NPS 1 to NPS 80 (DN25 to DN2000)                 |
| Pressure Rating | CL150 to CL2500                                  |
| Body Material   | A105; A106 Gr. B; A182 F11 / F22; A335 P11 / P22 |
| Nozzle Material | SS 316 / SS 410 (Stellited Optional)             |
| Type            | Separate Control Valve / In-built Control Valve  |
| Turndown        | 4:1 to 40:1                                      |



## PRDS STATION / PRESSURE REDUCING STATION

|                          |                                   |
|--------------------------|-----------------------------------|
| Inlet x Outlet Pipe Size | NPS 1 to NPS 24 x NPS 1 and above |
| Pressure Rating          | CL150 to CL2500                   |
| Piping Material          | A106 Gr. B; A335 P11 P22 / P91    |
| End Connections          | Flanged / Socket Weld / Butt Weld |
| Configuration            | Separate CV & DSH / Combined PRDS |



## TURBINE BYPASS VALVE / COMBINED PRDS VALVE

|                     |                                                |
|---------------------|------------------------------------------------|
| Inlet x Outlet Size | NPS 1 to NPS 24 x NPS 1 and above              |
| Pressure Rating     | CL150 to CL2500                                |
| Body Material       | A216 WCB; A217 WC6 / WC9; A105; A182 F11 / F22 |
| End Connections     | Flanged / Socket Weld / Butt Weld              |
| Leakage Class       | Class IV / Class V                             |
| Operation           | Pneumatic / Motorized / Electro-Hydraulic      |
| Body Configurations | Globe / Angle                                  |



## QUICK CLOSING NON-RETURN VALVE (QCNRV)

|                 |                                     |
|-----------------|-------------------------------------|
| Size            | NPS 4 to NPS 24 (DN100 to DN600)    |
| Pressure Rating | CL150 to CL600                      |
| Service Media   | Steam / Water / Gas                 |
| End Connections | Flanged / Butt Weld                 |
| Body Material   | A216 WCB; A217 WC6 / WC9; A351 CF8M |
| Operation       | Pneumatic                           |

# Our Global Presence



Argentina | Bangladesh | China | Chile | Ethiopia | Egypt | Honduras | Iran | Indonesia | Kenya  
 Malaysia | Mexico | Nigeria | Philippines | Portugal | Poland | Russia | Sri Lanka | Saudi Arabia South  
 Africa | South Korea | Turkey | Thailand | Tunisia | UAE | UK | USA | Vietnam

## We are Trusted By



**HEAD OFFICE**

**FACTORY**

**INNOVATION  
CENTRE**

21, Shubham, Prosperity Society, Karve Nagar, Pune - 411052  
 Tel: +91 20 25420021, 9518330514, 7066040407, 7030530022  
 Email: [info@inditechvalves.com](mailto:info@inditechvalves.com)

Plot No. 5, Gate No. 171, 172 & 177, Village Dhanore, Alandi-Markal  
 Road, Pune - 412105, India

Plot No. D102, KSSIDC Industrial Estate, Gamanagatti,  
 Hubli - 580026, India